

Outside Diameter (mm)	x	Wall (mm)	Average Wall or Minimum	Outside Diameter (inches)	Wall (inches)	Gauge	Inside Diameter (mm)	1.4401, 1.4404, 316, 316L	1.4571, 316Ti	1.4435, 316L	1.4301, 1.4307, 304, 304L	1.4541, 321
1.24	x	0.200	AW		0.008		0.840	•				
2.50	x	0.200	AW		0.008		2.100	•				
3.00	x	0.250	AW				2.500	•				
3.00	x	0.300	AW				2.400	•				
3.00	x	1.000	AW				1.000	•				
3.18	x	0.150	AW	1/8			2.880				•	
3.18	x	0.406	AW	1/8	0.016		2.368	•			•	
3.18	x	0.560	AW	1/8	0.022	24	2.060	•				
3.18	x	0.710	AW	1/8	0.028	22	1.760	•				
3.18	x	0.910	AW	1/8	0.036	20	1.360	•				
4.00	x	0.500	AW				3.000	•				
4.00	x	1.000	AW				2.000	•				
4.50	x	0.500	AW				3.500	•				
4.76	x	0.510	AW	3/16	0.020	25	3.740	•		•		
4.76	x	0.560	AW	3/16	0.022	24	3.640	•				
4.76	x	0.710	AW	3/16	0.028	22	3.340	•				
4.76	x	0.910	AW	3/16	0.036	20	2.940	•			•	
5.00	x	0.500	AW				4.000	•	•			
5.00	x	1.000	AW				3.000	•	•			
6.00	x	0.500	AW				5.000	•	•			•
6.00	x	0.750	AW				4.500	•				
6.00	x	1.000	AW				4.000	•	•		•	•
6.00	x	1.500	AW				3.000	•	•		•	•
6.00	x	2.000	AW				2.000	•	•			
6.35	x	0.510	AW	1/4	0.020	25	5.330	•				
6.35	x	0.710	AW	1/4	0.028	22	4.930	•				
6.35	x	0.910	AW	1/4	0.036	20	4.530	•				
6.35	x	1.240	AW	1/4	0.049	18	3.870	•				
6.35	x	1.650	AW	1/4	0.065	16	3.050	•			•	
7.00	x	1.000	AW				5.000	•				
7.94	x	0.710	AW	5/16	0.028	22	6.520	•				
7.94	x	0.910	AW	5/16	0.036	20	6.120	•				
7.94	x	1.240	AW	5/16	0.049	18	5.460	•				
8.00	x	0.500	AW				7.000	•			•	
8.00	x	1.000	AW				6.000	•	•	•	•	•
8.00	x	1.500	AW				5.000	•	•		•	•
8.00	x	2.000	AW				4.000	•	•		•	
9.00	x	1.000	AW				7.000	•				•
9.53	x	0.710	AW	3/8	0.028	22	8.105	•				
9.53	x	0.910	AW	3/8	0.036	20	7.705	•			•	
9.53	x	1.240	AW	3/8	0.049	18	7.045	•				
9.53	x	1.650	AW	3/8	0.065	16	6.225	•				
9.53	x	2.110	AW	3/8	0.083	14	5.305	•				
9.53	x	2.640	AW	3/8	0.104	12	4.245	•				
10.00	x	1.000	AW				8.000	•	•		•	•
10.00	x	1.500	AW				7.000	•	•		•	•
10.00	x	2.000	AW				6.000	•	•		•	
11.00	x	2.000	AW				7.000	•				
11.11	x	0.910	AW	7/16	0.036	20	9.290	•				
12.00	x	1.000	AW				10.000	•	•		•	•
12.00	x	1.500	AW				9.000	•	•	•	•	•
12.00	x	2.000	AW				8.000	•	•		•	•
12.00	x	2.500	AW				7.000	•				
12.70	x	0.710	AW	1/2	0.028	22	11.280	•				
12.70	x	0.910	AW	1/2	0.036	20	10.880	•			•	
12.70	x	1.240	AW	1/2	0.049	18	10.220	•		•	•	
12.70	x	1.650	AW	1/2	0.065	16	9.400	•			•	
12.70	x	2.110	AW	1/2	0.083	14	8.480	•			•	
12.70	x	2.640	AW	1/2	0.104	12	7.420	•			•	
12.70	x	3.250	AW	1/2	0.128	10	6.200	•				
14.00	x	1.000	AW				12.000	•	•			
14.00	x	1.500	AW				11.000	•				
14.00	x	2.000	AW				10.000	•	•			•
15.00	x	1.000	AW				13.000	•	•		•	•
15.00	x	1.500	AW				12.000	•	•		•	•
15.00	x	2.000	AW				11.000	•	•			•

Outside Diameter (mm)	x	Wall (mm)	Average Wall or Minimum	Outside Diameter (inches)	Wall (inches)	Gauge	Inside Diameter (mm)	1.4401, 1.4404, 316, 316L	1.4571, 316Ti	1.4435, 316L	1.4301, 1.4307, 304, 304L	1.4541, 321
15.88	x	0.910	AW	5/8	0.036	20	14.060	•			•	
15.88	x	1.240	MW	5/8	0.049	18	13.400	•			•	
15.88	x	1.650	MW	5/8	0.065	16	12.580	•			•	
15.88	x	2.110	MW	5/8	0.083	14	11.660	•			•	
15.88	x	3.250	AW	5/8	0.128	10	9.380	•			•	
16.00	x	1.000	AW				14.000	•			•	
16.00	x	1.500	AW				13.000	•	•			
16.00	x	2.000	AW				12.000	•	•			•
16.00	x	3.000	AW				10.000	•		•		
18.00	x	1.000	AW				16.000	•	•			
18.00	x	1.500	AW				15.000	•	•		•	•
18.00	x	2.000	AW				14.000	•	•			•
19.05	x	0.910	AW	3/4	0.036	20	17.230	•			•	
19.05	x	1.240	MW	3/4	0.049	18	16.570	•			•	
19.05	x	1.650	MW	3/4	0.065	16	15.750	•			•	•
19.05	x	2.110	MW	3/4	0.083	14	14.830	•			•	
19.05	x	2.640	AW	3/4	0.104	12	13.770	•				
19.05	x	3.250	AW	3/4	0.128	10	12.550	•				
20.00	x	1.000	AW				18.000	•	•		•	
20.00	x	1.500	AW				17.000	•	•		•	
20.00	x	2.000	AW				16.000	•	•		•	•
20.00	x	2.500	AW				15.000	•				
20.00	x	3.000	AW				14.000	•	•			
22.00	x	1.000	AW				20.000	•				
22.00	x	1.500	AW				19.000	•	•	•		
22.00	x	2.000	AW				18.000	•				
22.22	x	1.240	AW	7/8	0.049	18	19.740	•				
22.22	x	1.650	AW	7/8	0.065	16	18.920	•				
22.22	x	3.250	AW	7/8	0.128	10	15.720	•				
25.00	x	0.500	AW				24.000	•				
25.00	x	1.500	AW				22.000	•	•		•	
25.00	x	2.000	AW				21.000	•	•			
25.00	x	2.500	AW				20.000	•				
25.00	x	3.000	AW				19.000	•	•			
25.40	x	0.910	AW	1	0.036	20	23.580	•				
25.40	x	1.240	MW	1	0.049	18	22.920	•			•	
25.40	x	1.650	MW	1	0.065	16	22.100	•			•	
25.40	x	2.110	MW	1	0.083	14	21.180	•			•	•
25.40	x	2.640	AW	1	0.104	12	20.120	•				
25.40	x	3.250	AW	1	0.128	10	18.900	•				
28.00	x	1.500	AW				25.000	•	•		•	
28.00	x	2.000	AW				24.000	•	•		•	
30.00	x	2.000	AW				26.000	•				
30.00	x	2.500	AW				25.000	•				
30.00	x	3.000	AW				24.000	•	•			
30.00	x	4.000	AW				22.000	•				
31.75	x	1.240	AW	1 1/4	0.049	18	29.270	•				
31.75	x	1.650	AW	1 1/4	0.065	16	28.450	•				
31.75	x	2.110	AW	1 1/4	0.083	14	27.530	•				
35.00	x	2.000	AW				31.000	•				
35.00	x	3.000	AW				29.000	•				
38.00	x	3.000	AW				32.000	•	•			
38.00	x	4.000	AW				30.000	•				
38.00	x	5.000	AW				28.000	•				
38.10	x	1.240	AW	1 1/2	0.049	18	35.620	•				
38.10	x	1.650	AW	1 1/2	0.065	16	34.800	•				
38.10	x	2.110	AW	1 1/2	0.083	14	33.880	•				
38.10	x	3.250	AW	1 1/2	0.128	10	31.600	•				
38.10	x	6.350	AW	1 1/2	0.250		25.400	•				
42.00	x	2.000	AW				38.000	•				
42.00	x	3.000	AW				36.000	•	•			
42.00	x	4.000	AW				34.000	•				
44.45	x	2.110	AW	1 3/4	0.083	14	40.230	•				
44.45	x	2.640	AW	1 3/4	0.104	12	39.170	•				
44.45	x	3.250	AW	1 3/4	0.128	10	37.950	•				
50.80	x	1.650	AW	2	0.065	16	47.500	•				
50.80	x	2.640	AW	2	0.104	12	45.520	•				
50.80	x	3.250	AW	2	0.128	10	44.300	•				
50.80	x	6.350	AW	2	0.250		38.100	•				

The tubes are manufactured and certified in accordance with the latest versions of each of the following specifications:

ASTM A269 | ASTM SA213 | ASME SA213 | EN10216-5 | NACE MR0175 | NACE MR0103 | AD2000-W2

Our stainless steel tubes are in bright annealed condition and lengths are 6000-6100mm